§ 250.1164

- (4) You must use and maintain the flare/vent meters for the life of the facility.
- (b) You must report all hydrocarbons produced from a well completion, including all gas flared, gas vented, and liquid hydrocarbons burned, to Office of Natural Resources Revenue on Form ONRR-4054 (Oil and Gas Operations Report), in accordance with 30 CFR 1210 102
- (1) You must report the amount of gas flared and the amount of gas vented separately.
- (2) You may classify and report gas used to operate equipment on the lease, such as gas used to power engines, instrument gas, and gas used to maintain pilot lights, as lease use gas.
- (3) If flare/vent meters are required at one or more of your facilities, you must report the amount of gas flared and vented at each of those facilities separately from those facilities that do not require meters and separately from other facilities with meters.
- (4) If flare/vent meters are not required at your facility:
- (i) You may report the gas flared and vented on a lease or unit basis. Gas flared and vented from multiple facilities on a single lease or unit may be reported together.
- (ii) If you choose to install meters, you may report the gas volume flared and vented according to the method specified in paragraph (b)(3) of this section.
- (c) You must prepare and maintain records detailing gas flaring, gas venting, and liquid hydrocarbon burning for each facility for 6 years.
- (1) You must maintain these records on the facility for at least the first 2 years and have them available for inspection by BSEE representatives.
- (2) After 2 years, you must maintain the records, allow BSEE representatives to inspect the records upon request and provide copies to the Regional Supervisor upon request, but are not required to keep them on the facility
- (3) The records must include, at a minimum:
- (i) Daily volumes of gas flared, gas vented, and liquid hydrocarbons burned:

- (ii) Number of hours of gas flaring, gas venting, and liquid hydrocarbon burning, on a daily and monthly cumulative basis;
- (iii) A list of the wells contributing to gas flaring, gas venting, and liquid hydrocarbon burning, along with gasoil ratio data:
- (iv) Reasons for gas flaring, gas venting, and liquid hydrocarbon burning; and
- (v) Documentation of all required approvals.
- (d) If your facility is required to have flare/vent meters:
- (1) You must maintain the meter recordings for 6 years.
- (i) You must keep these recordings on the facility for 2 years and have them available for inspection by BSEE representatives.
- (ii) After 2 years, you must maintain the recordings, allow BSEE representatives to inspect the recordings upon request and provide copies to the Regional Supervisor upon request, but are not required to keep them on the facility.
- (iii) These recordings must include the begin times, end times, and volumes for all flaring and venting incidents
- (2) You must maintain flare/vent meter calibration and maintenance records on the facility for 2 years.
- (e) If your flaring or venting of gas, or burning of liquid hydrocarbons, required written or oral approval, you must submit documentation to the Regional Supervisor summarizing the location, dates, number of hours, and volumes of gas flared, gas vented, and liquid hydrocarbons burned under the approval.

\S 250.1164 What are the requirements for flaring or venting gas containing H_2S ?

- (a) You may not vent gas containing $\rm H_2S$, except for minor releases during maintenance and repair activities that do not result in a 15-minute time-weighted average atmosphere concentration of $\rm H_2S$ of 20 ppm or higher anywhere on the platform.
- (b) You may flare gas containing $\rm H_2S$ only if you meet the requirements of §§ 250.1160, 250.1161, 250.1163, and the following additional requirements:

- (1) For safety or air pollution prevention purposes, the Regional Supervisor may further restrict the flaring of gas containing H_2S . The Regional Supervisor will use information provided in the lessee's H_2S Contingency Plan ($\S250.490(f)$), Exploration Plan, DPP, DOCD submitted to BOEM, and associated documents to determine the need for restrictions: and
- (2) If the Regional Supervisor determines that flaring at a facility or group of facilities may significantly affect the air quality of an onshore area, the Regional Supervisor may require you to conduct an air quality modeling analysis, under 30 CFR 550.303, to determine the potential effect of facility emissions. The Regional Supervisor may require monitoring and reporting, or may restrict or prohibit flaring, under 30 CFR 550.303 and 30 CFR 550.304.
- (c) The Regional Supervisor may require you to submit monthly reports of flared and vented gas containing H_2S . Each report must contain, on a daily basis:
- (1) The volume and duration of each flaring and venting occurrence;
- (2) H₂S concentration in the flared or vented gas; and
- (3) The calculated amount of SO_2 emitted.

OTHER REQUIREMENTS

§ 250.1165 What must I do for enhanced recovery operations?

- (a) You must promptly initiate enhanced oil and gas recovery operations for all reservoirs where these operations would result in an increase in ultimate recovery of oil or gas under sound engineering and economic principles.
- (b) Before initiating enhanced recovery operations, you must submit a proposed plan to the BSEE Regional Supervisor and receive approval for pressure maintenance, secondary or tertiary recovery, cycling, and similar re-

covery operations intended to increase the ultimate recovery of oil and gas from a reservoir. The proposed plan must include, for each project reservoir, a geologic and engineering overview, Form BOEM-0127, and supporting data as required in §250.1167, 30 CFR 550.1167, and any additional information required by the BSEE Regional Supervisor.

(c) You must report to Office of Natural Resources Revenue the volumes of oil, gas, or other substances injected, produced, or produced for a second time under 30 CFR 1210.102.

§ 250.1166 What additional reporting is required for developments in the Alaska OCS Region?

- (a) For any development in the Alaska OCS Region, you must submit an annual reservoir management report to the Regional Supervisor. The report must contain information detailing the activities performed during the previous year and planned for the upcoming year that will:
- (1) Provide for the prevention of waste;
- (2) Provide for the protection of correlative rights; and
- (3) Maximize ultimate recovery of oil and gas.
- (b) If your development is jointly regulated by BSEE and the State of Alaska, BSEE and the Alaska Oil and Gas Conservation Commission will jointly determine appropriate reporting requirements to minimize or eliminate duplicate reporting requirements.
 - (c) [Reserved]

§ 250.1167 What information must I submit with forms and for approvals?

You must submit the supporting information listed in the following table with the form identified in column 1 and for the approvals required under this subpart identified in columns 2 through 4:

	WPT BSEE- 0126 (2 copies)	Gas cap pro- duction	Downhole commingling	Production within 500-ft of a unit or lease line
(a) Maps: (1) Base map with surface, bottomhole, and completion locations with respect to the unit or lease line and the orientation of representative seismic lines or cross-sections.		,		